



John C Wilkins
Acoustic Supplies

DATA SHEET

JCW IMPACTA 4551

THE PRODUCT

The most economical of materials, JCW's Impacta 4551 has a host of other benefits. It is made from 100% recycled materials – ideal for those specifiers who must adhere to environmental obligations. It reduces construction heights but can still take services and will bond to any floor finish. It is incredibly quick and easy to install, and offers long term, market-leading performance. Impacta 4551 complies with Part E of the Building Regulations.

THE FACTS

- Robust acoustic underlay material that attenuates impact sound at source.
- Suitable for new build or refurbishment projects.
- Suitable with concrete or screeded sub floor.
- Suitable for all floor finishes including: vinyl, wood, laminates, carpet, ceramic tiles, marmoleum and linoleum.
- Suitable for use with underfloor heating.
- Has zero ODP (Ozone Depletion Potential) and zero GWP (Global Warming Potential).
- Accepted by NHBC for ADE compliance.
- Standard thickness 3.0mm; other thicknesses available.
- Following extensive testing, JCW Impacta Adhesive is recommended to bond the product to the base floor.



SPECIFICATION

Depth	3mm (Other thicknesses available)
Roll size	19m ²
Impact sound insulation: (measured in accordance with BS EN ISO 140 – 8: 1998)	dBΔLw: 19dB

INSTALLATION

Please find all installation advice in our separate guide.

For expert installation, we offer our own installation service anywhere in the UK. Your installation will be performed to the highest standards by skilled and experienced tradesmen. These experts understand the importance of fitting acoustic materials absolutely perfectly, and they have the specialist skills to ensure your JCW materials are fitted correctly every time. As they are both experienced and skilled, they are also able to provide a highly efficient and extremely cost-effective service.

For further details, call John C Wilkins Acoustic Installations on 01204 387 029.