

Product data sheet

Glasroc® X Sealing Tape White

Glasroc® X Sealing Tape White is a self-adhesive high performance sealing tape.

Where to use

Use it to seal flat joints and exposed edges specifically on Glasroc X Sheathing Board and helps protect exposed linings from the elements for six months.



Product information

Composition

This product is a self adhesive multi-layer polymer tape.

Colour

White with blue printing.

Lengths available (m)

25.

Width (mm)

60.

Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

Standards

No harmonised standard.

Reaction to fire	E
------------------	---

Installation guidance

Limitations of use

Please note that Glasroc® X Sealing Tape White should only be used with Glasroc X Sheathing Boards. The tape should not be installed in temperatures below -10 °C or higher than +45 °C.

Cutting

Cut the product to size using a knife or scissors.

Application

Before installation of the tape, be sure that joints are dry and free from oil, grease and dust.

- Remove the protective film. Working upwards from the bottom apply Glasroc® X Sealing Tape White centrally to the vertical joints up to the lowest horizontal joint. Apply sufficient pressure to ensure good adhesion.
- Apply Glasroc® X Sealing Tape White centrally to the horizontal joint, overlapping the vertical joint tape by a minimum of 15 mm.

c. Tape the next vertical joint above, overlapping the horizontal joint tape by a minimum of 25 mm.

d. When splicing tape, there must be an overlap of approx. 50 mm.

It is recommended to use a suitable roller across the tape to ensure good adhesion.

Exposed edges or window openings

If using Glasroc® X Sealing Tape White to temporarily protect exposed edges or window openings, Ethylene Propylene Diene Monomer (EPDM) is not required before window framing is installed.

EPDM will still be required for sufficient sealing between Glasroc X Sheathing Boards and window framing.

Finishing

Please consult the Glasroc X Sheathing Board Installation Guide for instructions. [Click here.](#)

Product data sheet

Glasroc® X Sealing Tape White

Sitework

Packaging overview

25 m roll in cardboard dispenser, 10 rolls per carton.

Quantity per carton	10 rolls
Quantity per pallet	42 cartons

Storage

Store in a dry place between 5 °C and 25 °C, keep out of sunlight and protect from frost.

Handling

British Gypsum fully accepts its responsibilities as a supplier of building materials and systems as required by Section 6 of the Health and Safety at Work etc. Act 1974.

To reduce manual handling risk, employers and workers should follow HSE's Manual Handling Operations Regulations 1992 (MHOR) and the HSE's guidance on manual handling at work (INDG143). Employers should carry out a risk assessment and implement control measures to avoid or minimise the need for manual handling. Workers should follow safe lifting and moving techniques and report any hazards.

Shelf life

24 months.

Environmental

Recyclability

This product can be recycled.

Disposal

Waste should be disposed of in accordance with local authority requirements.



"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Okarno Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.