

## XFLO® FF

Foil Faced High Compressive Strength Underfloor Heating Floorboard



### Product Information

XFLO® FF under floor heating insulation boards have a high compressive strength and aluminium foil facing for added thermal diffusion. The boards are manufactured to suit the pipe diameter and spacing required and once covered with **ScreedBoard® 20** provide a responsive heating solution for domestic and commercial applications.

### Product Benefits

- ⊗ High resistance to compression - 250, 300 & 500kPa
- ⊗ Aluminum foil facing for improved heat diffusion
- ⊗ Manufactured to suit pipe and output requirements

### Technical Data

		XFLO® FF		
		250	300	500
Product description	-	Foil faced, high strength underfloor heating board		Ultra strength foil faced brd
Strength at 10% compression	kPa	250	300	500
Thermal conductivity	W/mK	0.033	0.033	0.035
Temperature range	°C	-50/+75	-50/+75	-50/+75
Route sizes available (to suit pipe diameter)	mm	10, 12, 14, 15, 16, 18, 20	10, 12, 14, 15, 16, 18, 20	10, 12, 14, 15, 16, 18, 20
Pipe centres	mm	150, 200, 300	150, 200, 300	150, 200, 300
Board size	mm	600 x 2500	600 x 2500	600 x 1250
Thickness' (other sizes manufactured to order)	mm	20, 25, 30, 35	40, 50, 60, 75	50, 60, 75

### Third Party Accreditation and Approvals



### Environmental Credentials

