

# UK Declaration of Performance

## EcoTherm Eco-Cavity

1000.UKDoP.ETEC.003

1001.UKDoP.ETEC.003

Unique identification code of the product-type:

Intended use/es:

Manufacturer:

System/s of AVCP:

Designated technical specification:

UK Assessment/Notified body/ies:

**EcoTherm Eco-Cavity**

**Thermal insulation for buildings**

**Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK**

**System 4 (Reaction to fire), System 3 (Other Properties)**

**BS EN 13165:2012+A2:2016**

**University of Salford: 1145, BBA: 0836**

Essential characteristics		Performance												
Thermal resistance	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	<table border="0"> <tr><td><math>d_N</math> 40mm</td><td>1.80</td></tr> <tr><td><math>d_N</math> 50mm</td><td>2.25</td></tr> <tr><td><math>d_N</math> 60mm</td><td>2.70</td></tr> <tr><td><math>d_N</math> 70mm</td><td>3.15</td></tr> <tr><td><math>d_N</math> 75mm</td><td>3.40</td></tr> <tr><td><math>d_N</math> 100mm</td><td>4.50</td></tr> </table>	$d_N$ 40mm	1.80	$d_N$ 50mm	2.25	$d_N$ 60mm	2.70	$d_N$ 70mm	3.15	$d_N$ 75mm	3.40	$d_N$ 100mm	4.50
	$d_N$ 40mm	1.80												
	$d_N$ 50mm	2.25												
$d_N$ 60mm	2.70													
$d_N$ 70mm	3.15													
$d_N$ 75mm	3.40													
$d_N$ 100mm	4.50													
Thermal conductivity $\lambda_D$ (W/(m.K))	$d_N$ 40mm- $d_N$ 100mm	0.022												
Thickness tolerance		T2												
Reaction to fire	Reaction to fire	F												
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market	NPD												
	Durability of thermal resistance and thermal conductivity against ageing/ degradation	NPD												
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	Thermal resistance as table above												
	Thermal conductivity $\lambda_D$ (W/(m.K))	0.022												
	Durability characteristics	NPD												
	Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1												
	Deformation under specified compressive load and temperature conditions	NPD												
	Determination of the aged values of thermal resistance and thermal conductivity	$\lambda_D$ 0,022 W/m.K												
Compressive strength	Compressive stress or compressive strength	CS(10Y)120												



Tensile / Flexural strength	Tensile strength perpendicular to faces	NPD
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Flatness after one sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Continuous Glowing combustion	Glowing combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2020.)

Signed for and on behalf of the manufacturer by:

.....  
Siobhan O'Dwyer  
Managing Director  
Pembridge, Selby, England, UK  
Date signed: 04/11/2025  
Issue Number: 003



For the most up-to-date version of the Declaration of Performance please scan or [click here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email [literature@kingspaninsulation.co.uk](mailto:literature@kingspaninsulation.co.uk)