

Declaration of Performance

Acoustic Partition Roll (APR 1200)



1 Unique identification code of the product type:	Acoustic Partition Roll (APR 1200)
2 Intended use/s:	Thermal Insulation for Buildings (ThIB)
3 Manufacturer:	Saint-Gobain Isover UK Limited Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU
4 Authorised representative:	N/A
5 System/s of AVCP:	System 1 (Reaction to fire) System 3
6 Covered by designated standard: Approved body/ies:	BS EN 13162:2012 + A1:2015 Approved body Warringtonfire Testing and Certification Limited No.1121 performed, carried out the determination of the product type, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance (1121-CPR-7001) for Reaction to fire.

Declaration of Performance

Acoustic Partition Roll (APR 1200)



7 Declared performance/s:

Harmonised Technical Specification: BS EN 13162:2012 + A1:2015

Essential characteristics	Performance	Unit	Declared Performance				
Product name			Acoustic Partition Roll (APR 1200)				
Reaction to fire		Euroclass	A1				
Release of dangerous substances to the indoor environment	Release of dangerous substances (e)		NPD				
Acoustic absorption index	Sound absorption		NPD				
Impact noise transmission index	Dynamic stiffness		NPD				
	Thickness		NPD				
	Compressibility		NPD				
	Air flow resistivity		NPD				
Direct airborne sound insulation index	Air flow resistivity		NPD				
Continuous glowing combustion	Continuous glowing combustion (e)		NPD				
Thermal resistance	Thermal resistance	m ² .K/W	0.60	1.25	1.60	1.70	2.30
	Thermal conductivity	W/m.K	0.039	0.039	0.040	0.043	0.043
	Thickness	mm	25	50	65	75	100
	Thickness class		T1	T1	T1	T1	T1
Water permeability	Short term water absorption		NPD				
	Long term water absorption		NPD				
Water vapour permeability	Water vapour transmission		NPD				
Compressive strength	Compressive stress or compressive strength		NPD				
	Point load		NPD				
Durability of Reaction to fire against heat, weathering, ageing/degradation	Durability characteristics (a)	Euroclass	A1				
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance (b)	m ² .K/W	0.60	1.25	1.60	1.70	2.30
	Thermal conductivity (b)	W/m.K	0.039	0.039	0.040	0.043	0.043
	Durability characteristics (c)		NPD				
Tensile/flexural strength	Tensile strength perpendicular to faces (d)		NPD				
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep		NPD				

NPD = No Performance Determined

- (a) No change in Reaction to fire properties for mineral wool products. The fire performance of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) For dimensional stability thickness only.
- (d) This characteristic also covers handling and installation.
- (e) European test methods are under development.

Declaration of Performance

Acoustic Partition Roll (APR 1200)



8 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

East Leake 27/11/2024

.....
Dean O'Sullivan, Managing Director, Isover

.....
Place and date of issue