

Knauf Vidiwall

Data Sheet



Knauf Vidiwall is a gypsum fibreboard manufactured from gypsum and cellulose fibres from recycled paper. This dense sheet material is suitable for all areas of drywall construction requiring a dense, impact resistant product capable of providing increased durability, rigidity and mechanical strength compared to a traditional gypsum sheet plasterboard.

Compliance: European Technical Approval ETA-07/0086 and EN 15283-2.

Storage and Handling

Product must be stored flat, and be protected from inclement weather.

Appropriate personal protective clothing and equipment etc. should be used when handling all Knauf boards.

Manual handling guidelines should be adhered to at all times.

This board is unsuitable for areas that are continuously damp, humid or above 50°C.

Performance Data

In compliance with EN 15283-2, the product is subject to initial type testing and continuous factory production control and bears the CE mark.

Technical Data

- Board weight and density:
12.5mm - 14.7kg/m² - 1180kg/m³
15mm - 17.7kg/m² - 1180kg/m³

For further product technical data, please refer to the Declaration of Performance.

Product Features

- Grey Face, Core and Reverse

Application / Installation

Use in accordance with BS 8000 British Standard Workmanship on building sites - Part 8: Code of practice for plasterboard partitions and dry linings.

Fix Knauf Vidiwall to the substrate with Knauf Vidiwall Screws.

All joints and screw heads, on every layer of Knauf Vidiwall, must be finished using Knauf Uniflott.

Apply Knauf Wallboard Primer to the face of Knauf Vidiwall prior to applying any finishes.

Related Products

- Knauf Metal Sections
- Knauf Vidiwall Screws
- Knauf Uniflott
- Knauf Tapes and Beads
- Knauf Sealant
- Knauf Intumescent and Acoustic Mastic
- Knauf Wallboard Primer

Health & Safety

May irritate eyes or sensitive skin.

Dust may irritate respiratory system.

- Protective gloves, glasses and face mask are recommended.
- Avoid inhaling dust when cutting / handling product. Ventilate area and move person to fresh air.
- Avoid ingestion – wash mouth out immediately and drink plenty of water.
- Should any symptoms persist or allergic reaction occur, seek medical advice.

Refer to the product MSDS and DoP on:
www.knauf.co.uk

Please turn over for product material numbers, dimensions and pallet details.

Stepped Edge



Dimensions (mm)			Material No.	Pallet Details		
Thickness	Width	Length		Boards	m ²	Tonnes (Approx.)
12.5	1200	2400	423072 ^{CF}	40	115.2	1.71
		2700	423072 ^{CF}	40	129.6	1.93
		3000	683472	45	162.0	2.40
15.0	1200	2400	423073 ^{CF}	35	100.8	1.80
		2700	423073 ^{CF}	35	113.4	2.02
		3000	423073 ^{CF}	35	126.0	2.25

Pallet weights exclude packaging.

Board weights and densities are for guidance purposes only and are subject to change.

Stated performance of plasterboard's are based on product characteristics and system testing using Knauf components.

For pricing details, please refer to the latest Knauf Price List.

^{CF} not able to order through EDI. Specific product configuration details required. Please contact Knauf Customer Services to order.

KML100247

Customer Service

UK Tel: 0800 521 050

Eire Tel: 01 4620739

Email: cservice@knauf.co.uk

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Technical Support

Live Webchat 09:00–17:00

Email: technical@knauf.co.uk

Knauf
87 Broomhill Road
Tallaght
Dublin
D24

Literature

UK Tel: 03700 613 700

Eire Tel: +44 3700 613 700

Website

www.knauf.co.uk

www.knauf.ie



KNAUF