

Product Data Sheet

Knauf Fill & Finish Light



Knauf Fill & Finish Light is a lightweight ready-mixed compound for bedding tapes and finishing joints in drywall partitions and ceilings. Delivers up to a Q4 finish.

Areas of Application

Gypsum plasterboards, for bedding paper tape and finishing second and third coat of joints. For bedding paper-faced and metal corner beads and finishing joints.

Compliance Standards

EN13963. Type 3A

Key Benefits

- Very low shrinkage finish
- Easy to sand
- Suitable for use with bazooka and banjo machine application
- Tub made from recycled plastic

Performance Data

Reaction to Fire (R2F)	Flexural Strength (F)	Density (g/cm ³)	Dangerous Substances (DS)
A2-s1,d0	pass (>320 N)	1.1 – 1.4	NPD

Technical information

Colour	Weight (kg)	Approximate Coverage (m ²)*	Material Number
Light cream/white	20	45 per 20kg tub	601440
Light cream/white	5	11.25 per 5kg tub	601462

*Based on filling application to tapered edge board

Sustainability

Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Volatile Organic Compound Content (VOC)

< 0.1% (<1 g/L).

Storage and Handling

Store in a well-ventilated place. Keep away from heat and ignition sources. Protect from freezing, high temperatures and direct exposure to sunlight. Not to be used under 5° air or surface temperatures.

Packaging

Recycled content plastic tub. Recyclable at the end of its life. Packed on a wooden pallet with PE shrink wrap.

Shelf Life/Service Life

12 months.

Disposal/Repair

Dispose of contents/container in accordance with licensed collectors sorting instructions. 17 09 04 - mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02, and 17 09 03.

Health & Safety

Ensure good ventilation, and wear personal protective equipment according to your risk assessment, see safety data sheet. Wear safety glasses with side shields due to splashing. When sanding, wear protective P2 dust mask. Impermeable protective gloves are recommended. Do not eat, drink or smoke when using this product. Always wash hands after handling.

Application / Installation

Stir to an even consistency before use, may be diluted to suit individual preferences. Ensure substrate is sound, dry, clean and free from oil, and dust. Drying time dependent upon thickness, temperature, ventilation, air humidity and type of substrate. Average drying time approximately 12-24 hours. Use a fine-grit sandpaper for surface sanding. Before application of paint or wallpaper, use an appropriate primer such as Knauf Wallboard Primer or Knauf Plasterboard Sealer.

Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

Datasheet for Indoor Air Quality available on request.



Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

0800 521050 (option 2)
Live Webchat 09:00 -17:00
technical-uk@knauf.com

Website

www.knauf.co.uk
www.knauf.ie

Address (UK)

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Address (Ireland)

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

KML100443

The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued.

© Copyright Knauf 2023

Creation Date: 08/06/2023

Revision Reference: 001

Revision Date: 08/06/2023