Declaration of performance
Majcoat 350 8750 – Vers.2.0
Nr. DoP-20-875-33

1. Unique identification / code of the product-type:

8750

2. Product labelling:

Majcoat 350

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification intended by the manufacturer:

Roof membrane and Facade membrane
Flexible sheets for waterproofing - Underlays for discontinuous roofing -
EN 13859-1:2010 and for walls - EN 13859-2:2010

4. Name and contact address of the manufacturer:

SIGA Cover AG
Rütmattstrasse 7
6017 Ruswil
Switzerland

5. Authorised representative:

-

6. System of assessment and verification of constancy of performance of the construction product:

AVCP System 3

7. Notified laboratory:

TECHNICKY A SKUSOBNY USTAV STAVEBNY n.O.
NB 1301
has carried out the assessment and verification according to system "3" and issued a test report.

8. Declared performance

Harmonized Technical Specification EN 13859-1:2010 & EN 13859-2:2010

Essential characteristic	Performance	Bottom tolerance	Top tolerance	Unit
Reaction to fire	**E** (surface-mounted)*			Class
Watertightness	**W1**			Class
Water vapour transmission Sd value	**0.3**	0.2	0.4	m
Maximum tensile force (lengthwise)	**440**	300	600	N/50mm
Maximum tensile force (crosswise)	**500**	300	750	N/50mm
Elongation at maximum tensile force (lengthwise)	**55**	20	100	%
Elongation at maximum tensile force (crosswise)	**45**	20	100	%
Tear propagation resistance (nail shank) (lengthwise)	**245**	225	400	N
Tear propagation resistance (nail shank) (crosswise)	**235**	225	370	N

Flexibility at low temperatures	**-40**			°C
Maximum tensile force (lengthwise) after ageing	**440**	300	600	
Maximum tensile force (crosswise) after ageing	**500**	300	750	
Elongation at maximum tensile force (lengthwise) after ageing	**55**	20	100	
Elongation at maximum tensile force (crosswise) after ageing	**45**	20	100	
Watertightness after ageing	**W1**			Class
Hazardous substances	**None**			

* Fire class tested on chipboard in accordance with EN 13238, valid for fitting with wood and wood-based materials as well as substrates of classes A1 or A2-s1, d0

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ruswil, 28.07.2025

Place, date

Seline Zürcher – Quality Management