

# STEICO *multi primer*

Solvent-free primer



## Solvent-free primer for porous substrates such as wood fibre boards

- Solvent free
- Can be processed from -10 °C
- High penetration
- Fast flash-off time, good water resistance
- Efficient material application thanks to practical dispenser bottle

### Application area



- Adhesion promotion / adhesion improvement of bonds with STEICO-*multi tape*

### Technical data

Processing temperature min. [°C]	- 10
Basis	aqueous acrylate polymer dispersion
Film property	Flexible (after curing)
Range for 1 kg [m]	+ STEICOmulti tape F 100mm approx. 35 m + STEICOmulti tape F 150mm approx. 25 m
Storage property (unopened) [months]	12
Airing time	approx. 14 (at +20°C / 50% relative humidity)

### Forms of delivery

#### Supplied in handy boxes

Form of delivery	Weight/piece [kg]	Size [ml]	Number/pack. [pcs.]
Bottle with dispenser	1.10	1000	6

### Weight and packing

#### Supplied in handy boxes

Weight/m <sup>2</sup> [kg]	Weight/pcs. [kg]	Weight/pack. [kg]	Packaging/pack. Paper/cardboard (approx.) [kg]
1.00	1.1	7.00	0.30

# STEICO *multi primer*

Solvent-free primer

## Notes

### Storage

- Store in a cool and dry place at +15 to +25 °C
- Protect from heat, cold and UV radiation

### Disposal

- Dispose of hardened material residues according to EWC 17 09 04 (mixed construction and demolition waste)

### Application method

- Brush or paint roller

### Occupational health and safety

- Additional information in the safety data sheet must be observed.

## Installation

- The substrate must be dry and free of grease and dust
- Shake the bottle well before use
- Apply the material to the substrate via the guide opening of the bottle and spread evenly with a brush or paint roller.
- Before applying and pressing on STEICO *multi tape*, allow the STEICO *multi primer* to flash off until transparent (colour change is permitted visual inspection)
- STEICO *multi primer* can be removed with water when fresh. When the primer has hardened, cleaning is generally only mechanically possible

## Certificates and quality management



# STEICO *multi primer*

Solvent-free primer

## ☰ Caption

### other abbreviations

- pal.** Pallet
- T&G** Tongue and Groove
- pac.** Packaging
- approx.** Approximately

### **Responsible for content**

STEICO SE  
Otto-Lilienthal-Ring 30  
85622 Feldkirchen  
Germany  
Web: [www.steico.com](http://www.steico.com)  
Mail: [info@steico.com](mailto:info@steico.com)

**Version: 1**

**Date: 2025-05-23**

The contents of this document have been prepared with the utmost care. However, applicable regulations can change. STEICO accepts no liability for the accuracy, completeness, or current applicability of the content. Application areas may vary in the detailing. Always verify the suitability of our products for the specific intended use.

The contents of this document have been prepared in consideration of European product standards and provide a general overview of component structures, construction methods, and installation. Local applicable regulations have not been considered. Before using our products, please verify that the applicable regulations for the specific area of use are followed.

The currently valid version can be found at: [www.steico.com/tds\\_steicomulti\\_primer\\_eur\\_en](http://www.steico.com/tds_steicomulti_primer_eur_en)