

# STEICO *multi tape P*

High performance tape with kraft paper



## High performance tape with kraft paper for internal use

- Solvent-free
- Temperature resistant between -40° and +100°
- Can be torn by hand
- Sturdy cardboard carrier
- Patches ideal for sealing injection holes

## Application area



- Joint and connection bonding in the STEICO membrane system, as on wood-based panels e.g. OSB

## Technical data

Temperature resistance [°C]	-40 / +100
Processing temperature [°C]	+5
Adhesive	Acrylic dispersion, solvent-free
Adhesive backing	Kraft paper with PE protective coating
Colour	White
Thickness (without release paper) [mm] (approx.)	0,3
Peeling strength	fulfilled according to DIN 4108/11
Peel strength after ageing	fulfilled according to DIN 4108/11

## Forms of delivery

Length [mm]	Width [mm]	Plaster [mm]	Number/roll [plaster]	Number/pack. [pcs.]
40000	60	-	-	10

### Roll with individual patches

Length [mm]	Width [mm]	Plaster [mm]	Number/roll [plaster]	Number/pack. [pcs.]
40000	200	180*180	222	1

# STEICO *multi tape P*

High performance tape with kraft paper

## Weight and packing

Length [mm]	Width [mm]	Weight/m <sup>2</sup> [kg]	Weight/pcs. [kg]	Weight/pack. [kg]	pac./pal. paper/cardboard (approx) [kg]
40000	60	1.09	1.1	11.50	0.50

### Roll with individual patches

Length [mm]	Width [mm]	Weight/m <sup>2</sup> [kg]	Weight/pcs. [kg]	Weight/pack. [kg]	pac./pal. paper/cardboard (approx) [kg]
40000	200	3.73	3.7	4.20	0.50

## Notes

### Storage

- Store in a cool and dry place at +5 to +25 °C
- Protect from heat, cold and UV radiation

### Ingredients

- Acrylic dispersion (solvent-free), kraft paper with PE protective coating

### Disposal

- dispose with normal construction waste, observe applicable legal guidelines

### Cutting

- Sharp knife or other suitable cutting tool

## Installation

- STEICO *multi tape P* can only be used indoors
- Substrates must be stable, dry, and free of dust and grease.
- Align STEICO *multi tape P* in the centre, remove the release paper step by step and rub the adhesive tape vigorously in the process
- Apply STEICO *multi tape P* without tension or creases. If tensile forces occur, the substrate must also be mechanically fastened.
- To improve adhesion, especially on wood-based panels, additional pressing with a pressure roller is recommended
- Bonding must not be in standing water. Bonding in saunas and swimming pools is also not permitted.

## Certificates and quality management



# STEICO *multi tape P*

High performance tape with kraft paper

## ☰ Caption

### other abbreviations

- pal.** Pallet
- T&G** Tongue and Groove
- pac.** Packaging
- approx.** Approximately

### **Responsible for content**

STEICO SE  
Otto-Lilienthal-Ring 30  
85622 Feldkirchen  
Germany  
Web: [www.steico.com](http://www.steico.com)  
Mail: [info@steico.com](mailto:info@steico.com)

**Version: 1**

**Date: 2025-05-23**

The contents of this document have been prepared with the utmost care. However, applicable regulations can change. STEICO accepts no liability for the accuracy, completeness, or current applicability of the content. Application areas may vary in the detailing. Always verify the suitability of our products for the specific intended use.

The contents of this document have been prepared in consideration of European product standards and provide a general overview of component structures, construction methods, and installation. Local applicable regulations have not been considered. Before using our products, please verify that the applicable regulations for the specific area of use are followed.

The currently valid version can be found at: [www.steico.com/tds\\_steicomulti\\_tapep\\_eur\\_en](http://www.steico.com/tds_steicomulti_tapep_eur_en)