



DECLARATION OF PERFORMANCE

SAFE-R 019

PHENOLIC
INSULATION

SR019/CW

1. Product Type

Unique identification code of the product type:

Safe-R 019 SR019/CW

2. Type

Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Batch No on board

3. Intended Use

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal Insulation for Buildings

4. Name, Registered Trade Name

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Unilin Insulation UK Ltd
Park Road, Holmewood
Chesterfield, Derbyshire
United Kingdom
S42 5UY

5. Contact Address

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 4)

6. AVCP

System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:

System 3

7. Approved Body

In case of the declaration of performance (DoP) concerning a construction product covered by a designated standard:

EN 13166:2012+A2:2016

Approved Body: BBA

Approved Body No.: 0836

Performed type testing under system 3 and issued test reports.

8. Technical Assessment Body (UKTA)

In case of the declaration of performance concerning a construction product for which a UK Technical Assessment (UKTA) has been issued:

Not relevant (see 7)

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield,
Derbyshire, UK, S42 5UY

T +44 (0) 371 222 1033
F +44 (0) 371 222 1044
E info.ui@unilin.com



DECLARATION OF PERFORMANCE

9. Declared Performance

Essential Characteristics	Performance			Test Standard	Harmonised Standard
Thermal Conductivity	0.019			EN 12667	
Reaction to Fire	Euroclass D s1 d0			EN 13501	
Thickness	T2			EN 823	
Length & Width	Dimensions < 1250 1250 to 2000 2001 to 4000 > 4000	Length ± 5,0 ± 7,5 ± 10,0 ± 15,0	Width ± 3,0 ± 7,5 ± 7,5 ± 10,0	EN 822	
Squareness	$S_b \leq 5\text{mm/m}$ $S_d \leq 2\text{mm/m}$			EN 824	EN 13166:2012 +A2:2016
Flatness	Nominal thickness mm < 50 50 to 100 > 100		Tolerances mm ≤ 10,0 ≤ 7,5 ≤ 5,0	EN 825	
Dimensional Stability	DS (70,90)			EN 1604	
Dimensional Stability	DS (N)			EN 1603	
Compressive Strength	CS (10\Y) 100			EN 826	

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Aidan Doyle, General Manager
Unilin Insulation UK Ltd.
01-01-2026

Unilin Insulation UK Ltd

Park Road, Holmewood, Chesterfield,
Derbyshire, UK, S42 5UY

T +44 (0) 371 222 1033
F +44 (0) 371 222 1044
E info.ui@unilin.com